



Fertilizer Injection Applicator





# Versatile, Tough... Built To Handle Any Terrain

- ▶ 4" X 6" Double Bar Mainframe & Wings
- ▶ 180 Degree Fold Extension Wings On 37' and 41' Applicators
- ▶ Hydraulic Wing Cylinder Rocker Plates
- ▶ Swath Widths From 27.5 to 42.5
- ▶ 38" Toolbar Rank
- ► Capable of 12 & 16 Row StripTill Operations
- ► 5 Year Frame Warranty



Runner II • LandRunner II • LandRunn LandRunner II • LandRunner II • Land

## LANDRUNNER II. Fertilizer Injection Applicator

Designed and built to rugged BLU-JET standards. The LANDRUNNER II's heavy 4" x 6" tubular framework with deep penetrating welds at critical points give you the strength to tackle any terrain. Versatile row spacing capabilities meet your needs for pre-plant, side-dress and striptill. Deep toolbar rank provides superior residue flow.



➤ 38" toolbar rank gives superior performance in heavy residue

Fully adjustable wheel tread on singles, duals, and walking tandem wheel assemblies with fully synchronized cylinders

Wheatland and clevis hitch choices match your needs while keeping the 30,400 lb. safety chain within ASAE standard

37' 15R30 180 Degree Fold Extension Wing

Large, 1-3/4" load bearing

wing hinge pins provide long life.

maximum flexibility and superior performance

#### **Specifications:**

5-Year Frame Warranty

Specifications:	standard
Mainframe	Heavy Duty 4" x 6" x 3/8" Mainframe
Tongue	6" x 4" Weighted A-Frame Tongue
Models	
Wheel Lift & Gauge Wheel Lift	Single Wheel Lift W/Single Gauge Wheel
ŭ	Dual Wheel Lift W/Hydraulic Single Gauge Wheel
	Walking Tandem Wheel Lift W/Tandem Gauge Wheel
Wheel Lift Tires & Rims	11L-15 12-Ply Single
	11L-15 8-Ply Duals and Walkers
	11L-15 12 Ply Duals and Walkers
Gauge Wheels Hydraulic Tires & Rims	11L-15 8-Ply Single Gauge Wheel Lift
,	11L-15 8-Ply Duals and Walkers
Gauge Wheels	
Gauge Wheel Tires Manual	25 x 7.50-15, 4 ply
Wing Flex	11 Degrees Down, 16 Degrees Up (Primary Wing)
Transport Width	16'-10" (17R30")
Transport Height	13'-4"
Row spacings	15,18, 30", or 36"
Coulters	Super 1200 Coulters with 20" Fluted Blades
Shanks	1" x 2" Flat, 1-1/4" x 2" Edge Bent
Clamps	Rigid, Spring Cushion, MaxPac
Optional	BLU-JET SealPro II Sealers
Sealer Blades	18" Hoe Wheel, 17" x 3/4" x 12" Wave, 17" Notched (Blunt)
Nurse Tank Hitch	BLU-JET AutoLok Nurse Tank Hitch
Distribution	John Blue Impellicone Manifold Distribution for GDI 200 or 9500 Meter
NH <sub>3</sub> Supply Connection	SuperShooter III Assembly (Less meter & Distribution)
Emergency Water Tank/Toolbox	
9000 lb./ Parking Jack	Standard
Lighting Kit	Standard

#### Find Out More...Call the BLU-JET Hotline (800-658-3127) Today

Thurston Manufacturing Company • 1708 H Ave • Box 218 • Thurston, Nebraska, 68062-0218 Phone: 402-385-3041 • Fax: 402-385-3043 • E-mail: box218@thurstonmfgco.com www.thurstonmfgco.com




### Your Partner for Conservation Farming



AutoLok nurse tank hitch has the largest hitching envelop in the industry, and it retracts for hitching and pulls out to latch NORUNNER II • LAND-



The BLU-JET Bodyguard on the exclusive SuperShooter III helps protect the operator from ammonia spray back during coupling. It features a multi-directional swivel and highly visible operational information



Mount BLU-JET StripTill Row Units on your LandRunner II for a 12 or 16 row StripTill applicator

Distributed By:



Form No. 15LRII-0610TM